

33"x48" Hand Pallet Lifter

Item code: GPC6600P00S

Main Features

Nominal load capacity : 5,004.44 lb
Frame material : Painted steel
Fork length : 48.03 in
Fork width : 6.30 in
Stowage passage : 74.88 in
Turning radius : 56.57 in

GS Special Series

The GS Special series, available in several versions, is the ideal working tool for moving nearly all sizes of pallet. Suitable for smooth floors or other kinds of surfaces, these pallet trucks guarantee easy and light manoeuvrability.

Technical specifications

Main specifications

Nominal load capacity 5,004.44 lb
Load center distance 23.62 in
Propelling system Manual
Driving system Pedestrian
Lifting system Manual
Frame material Painted steel
Compliance certification CE

Performances

Operating brake n.a.
Parking brake n.a.
Lifting speed, without load 13 strokes
Lifting speed, with load 13 strokes
Lowering speed, without load 0,05 m/s
Lowering speed, with load 0,1 m/s
Lowering speed, without load - second speed n.a.
Lowering speed, with load - second speed n.a.

Dimensional Data

Lift height 6.50 in
Normal free lifting 4.53 in
Fork length 48.03 in
Fork width 6.30 in
Forks thickness 1.54 in
Lowered forks height 1.97 in
Overall width 32.87 in
Overall length 63.78 in
Overall height (handle) 45.67 in
Stowage passage 74.88 in
Turning radius 56.57 in
Drive unit length 15.75 in
Frame, wheel base 49.68 in

Frame, load axle to end forks 8.46 in

Wheels

Front wheels width 1.77 in
Front wheels diameter 7.87 in
Front wheels material Polyurethane, nylon
Front track 5.71 in
Rear wheels number 2
Rear wheels width 3.23 in
Rear wheels diameter 1.97 in
Rear wheels material Steel
Rear track 14.37 in
Rear balancing axle No

Other Equipment

Entry/exit system No

Weights

Weight without load 200.62 lb
Front axle load, without load 132.28 lb
Front axle load, with load 1,554.24 lb
Rear axle load, without load 68.34 lb
Rear axle load, with load 3,055.58 lb

Additional information

Operating conditions: minimum temperature -12 °C
Operating conditions: maximum temperature 50 °C

Technical specifications are subject to change without notice. Consult your local Lifter representative for more information.