

Basic-Version (FL-EB 200)

- Install the HP-gun (a) with the preinstalled adapter (b) to the swivel (c).
 - Note: Install the HP-gun (a) in a 90° angle to the handle (d) (see top view).

Standard-Version

Δ

1. Install the wand (e) to the quick-connect (f).

Standard-Version short

- 1. To use the short version with toggle swivel (g), detach the HP-gun (a) from the wand (e).
- 2. Detach the extension piece (h) including wand (e) from the toggle swivel (g).
- 3. Install the HP-gun (a) directly to the toggle swivel (g).
- 4. Use bolt (i) and nut (j) to install the handle (d) to the housing (k).
- Note: Install the HP-gun (a) in a 90° angle to the handle (d) (see top view).

For your own safety

 Λ

- Read all instructions before the initial operation. Check their proper condition and that they operate safely.
- Always use protection gear when using products connected to high pressure.
- Before any maintenance or nozzle-change, turn off the high pressure water supply, e.g.: turn off and secure the power switch.
- After turning off the system, allow all self propelled equipment to come to a complete stop before handling.
- Safety regulations and guidelines (Accident Prevention Rules) from the manufacturer of your high pressure cleaner are applicable.
- Nozzle installation according to nozzle manufacturer.
- Do not move the unit over objects or uneven surfaces.
- Do not lift up the unit while operating.
- Do not run the unit if spray-arm is out of balance or bent, damage to the swivel will result.
- No modifications to the unit are permitted.

