

## **Electric Pallet Truck**

### **Item code: EC245500000**

#### **Main Features**

Nominal load capacity : 3,086.44 lb  
Driving system : Pedestrian  
Fork length : 45.28 in  
Fork width : 5.91 in  
Traction motor nominal power : 0,7 kW  
Minimum admitted battery capacity : 70 Ah

#### **CX14 Series**

The CX14 powered truck is available in several versions fitted with MOSFET technology. They are suitable for carrying loads on smooth floors and other surfaces. The small size and turning radius make the CX14 range ideal for work in areas where space is at a premium, such as lorries or narrow aisles.

#### **Technical specifications**

##### **Main specifications**

Nominal load capacity 3,086.44 lb  
Load center distance 23.62 in  
Propelling system Electric  
Driving system Pedestrian  
Lifting system Electric  
Compliance certification CE

##### **Performances**

Operating brake Reverse current braking  
Parking brake Electromagnetic  
Travel speed, without load 4,7 km/h  
Travel speed, with load 4,5 km/h  
Travel speed with lowered platform, without load n.a.  
Travel speed with lowered platform, with load n.a.  
Lifting speed, without load 0,03 m/s  
Lifting speed, with load 0,02 m/s  
Lowering speed, without load 0,04 m/s  
Lowering speed, with load 0,04 m/s  
Maximum gradient, without load 10 %  
Maximum gradient, with load 5 %

##### **Dimensional data**

Lift height 7.87 in  
Normal free lifting 4.53 in  
Fork length 45.28 in  
Overall forks width 26.97 in  
Fork width 5.91 in  
Forks thickness 1.97 in  
Lowered forks height 3.35 in  
Overall width 28.35 in  
Overall length 64.96 in  
Height, lowered mast n.a.

Height, extended mast n.a.  
Overall length with raised platform n.a.  
Overall length with lowered platform n.a.  
Stowage passage 74.80 in  
Turning radius 56.50 in  
Stowage passage with lowered platform n.a.  
Stowage passage with raised platform n.a.  
Turning radius with lowered platform n.a.  
Turning radius with raised platform n.a.  
Drive unit length 19.69 in  
Drive unit length with lowered platform n.a.  
Drive unit length with raised platform n.a.  
Frame, wheel base 47.05 in  
Frame, load axle to bulkhead 8.46 in

### **Wheels**

Front track 19.53 in  
Front - traction wheel width 2.99 in  
Front - traction wheel diameter 9.84 in  
Front - traction wheel material Rubber  
Front - stabilizers wheels number 2  
Front - stabilizers wheels width 1.97 in  
Front - stabilizers wheels diameter 3.94 in  
Front - stabilizers wheels material Polyurethane  
Rear wheels number 2  
Rear wheels width 3.15 in  
Rear wheels diameter 3.23 in  
Rear wheels material Polyurethane  
Rear track 21.06 in

### **Electric Equipment**

Traction motor nominal power 0,7 kW  
Traction speed control system MOSFET  
Traction motor excitation system Permanent magnet  
Lifting motor nominal power 0,4 kW  
Lifting motor excitation system Series excitation  
Battery type Traction  
Battery voltage 24 V  
On-board battery charger voltage 24 V  
On-board battery charger current 20 A  
Minimum admitted battery capacity 70 Ah  
Maximum admitted battery capacity 110 Ah  
Minimum admitted battery weight 171.96 lb  
Maximum admitted battery weight 220.46 lb  
Battery discharge protection device Yes  
Battery status indicator Yes  
Hourmeter Yes

### **Other Equipment**

Entry/exit system Yes

### **Weights**

Weight without load, with platform (battery included) n.a.  
Weight without load, without platform (battery included) 551.15 lb

Front axle load, without load 462.97 lb  
Front axle load, with load 1,327.17 lb  
Rear axle load, without load 88.18 lb  
Rear axle load, with load 2,310.42 lb

**Additional information**

Operating conditions: minimum temperature 0 °C  
Operating conditions: maximum temperature 40 °C  
Electric protection grade IP 20

Technical specifications are subject to change without notice. Consult your local Lifter representative for more information.