

## INSTRUCTIONS:

1. Clean or Replace cartridges at consistent 25psi running pressure.
2. Drain water in bulk supply tank daily (Use Sump pump or gravity drain) to prevent bacterial contamination or treat with chlorine – DO NOT drink water! Dispose of gray water properly and with proper permits as required by your local regulations.
3. Drain hopper in to 5-gallon bucket; replace oil skimmer absorber as required, dispose of sludge properly at Hazardous Materials collection center (Do Not exceed 6" of sludge in hopper). Drain Hopper before towing if unit is trailer mounted.
4. Bag filters can be cleaned and reused until plugged. Clean daily (or every 8 hours of use which ever is less)
5. Replace Carbon Filter monthly or after 40 hrs usage as required. Replace or clean cartridge filters daily or more often under sever conditions. (Keep a large supply of replacement filters on hand)
6. Do not use soap or other additives.
7. If optional sump pump is on but will not pump, remove discharge hose and run pump to allow it to prime itself.

## Notes:

- Minimum requirements 12 volt / 15 amp Engine charging system and 12 volt battery. 185-gallon bulk supply tank with 8" lid.
- Drain all tanks and clean or replace cartridges daily, use Hydro Tek replacements or exact equivalents to avoid damage to the pressure washer.

## Replacement Parts

### Part Number Description

- VFH07 Cartridge, 4.5" x 20" - 20 micron
  - VFH10 Cartridge, 4.5" x 20" - 10 micron-carbon
  - VB040 Oil Skimmer Bag
  - VFB10 Bag Filter 7 x 32 - 100 micron
  - VFB05 Bag Filter 7 x 32 - 5 micron
  - VF007 Optional Sump Pump Strainer/Filter
  - PS110 Optional Sump Pump 110v
  - PS120 Transfer Pump 12v DC
  - VG006 60psi Bottom Mount Gauge
  - ZMAT6 Optional Sand Bag Dam 10'
  - ZMAT1 Optional Water Tube Dike 10'
- Call for pricing on bulk packs

Call Greg Cross (ext: 212) to order

